

# MATERIAL SAFETY DATA SHEET

## SECTION I/ IDENTIFICATION OF MATERIAL

**Product Name: Citrus Strip**

**USE: CLEANER AND STRIPPER**

**DISTRIBUTOR INFORMATION:** Concrete Texturing Tool and Supply

45 Underwood Road  
Throop, PA. 18512  
570-489-6025

**HAZARDOUS CONTACT: CHEM-TEL**

**EMERGENCY PHONE NUMBER: 800-255-3924**

## SECTION II/ HAZARDOUS INGREDIENTS

<u>COMPONENT</u>	<u>CAS #</u>	<u>%</u>	<u>OSHA PEL</u>
Medium Aliphatic Solvent naptha	64742-88-7	30-50	100 ppm
Ethylene Glycol Ether	111-76-2	5-10	50 ppm 240 mg/m3

## SECTION III/ PHYSICAL DATA

<b>APPEARANCE &amp; ODOR</b>	Clear, colorless to pale yellow. Citrus
<b>EVAPORATION RATE</b>	<.1 (butyl acetate = 1)
<b>VAPOR DENSITY</b>	5.3 (AIR 1)
<b>% VOLATILE BY WEIGHT</b>	100%
<b>VAPOR PRESSURE</b>	<5 mmHG at 100° F
<b>SOLUBILITY IN WATER</b>	Negligible
<b>BOILING POINT</b>	355-395° F
<b>SPECIFIC GRAVITY</b>	.76
<b>VISCOSITY</b>	N/A

## SECTION IV/ FIRE FIGHTING MEASURES

<b>FLASHPOINT</b>	110° F
<b>FLAMMABLE LIMITS</b>	1-7%      LOWER 1%      UPPER 7%
<b>EXTINGUISH MEDIA:</b>	WATER FOG, FOAM MIST, CO 2, DRY CHEMICAL

**SPECIAL PROCEDURES:** Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling. Use self contained breathing apparatus with full face piece and protective clothing.

**USUAL FIRE AND EXPLOSIVE HAZARDS:** Product is flammable and may be ignited by heat, sparks, flames, or other sources of ignition. Vapors may travel a considerable distance to a source of ignition where they can ignite, flashback, or explode. May create vapor/air explosion

**hazard indoors, outdoors, or in sewers. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled it can explode in the heat of fire.**

---

#### **SECTION V/EFFECTS OF OVEREXPOSURE**

---

**CARCINOGENICITY:**

**NTP: NONE**

**IARC: NONE**

**OSHA REGULATED: NONE**

---

#### **SECTION VI/ REACTIVITY DATA**

---

**STABILITY: STABLE**

**CONDITIONS TO AVOID: EXTREME HEAT AND IGNITION SOURCE**

**INCOMPATIBILITY: STRONG OXIDIZING AGENTS**

**HAZARDOUS DECOMPOSITION PRODUCTS:**

**CO,CO<sub>2</sub>,AND VARIOUS HYDROCARBONS UNDER FIRE  
CONDITIONS**

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR**

---

#### **SECTION VI/ HEALTH HAZARD DATA**

---

**THRESHOLD LIMIT VALUE: See section II for components**

**ROUTE OF ENTRY: Contact and Inhalation primary. Ingestion possible.**

---

#### **SECTION VII/ FIRST AID**

---

**DERMAL Wash with warm water and mild soap. Remove contaminated clothing.**

**EYE Flush with water for 15 minutes or until irritation subsides.**

**INHALATION N/A**

**INGESTION Do NOT induce vomiting. Seek medical attention**

---

**\*\*IF IRRITATION OR RESPIRTORY PROBLEMS PERSIST SEEK  
MEDICAL ATTENTION IMMEDIATELY. IF PROLONGED  
EXPOSURE OCCURS CONSULT YOUR PHYSICIAN  
IMMEDIATELY\*\***

---

#### **SECTION VIII/ HANDLING & STORAGE**

---

**IF MATERIAL IS RELEASED OR SPILLED: Keep all sources of ignition and hot metal surfaces away from spill/release. Evacuate all unprotected personnel from area. Use foam on spills to minimize vapors. Contain spill if it can be done with minimal risk. Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Prevent liquid from entering drains, sewers, or waterways. Notify proper authorities.**

**WASTE DISPOSAL: Follow federal, state, and local regulations. Meets ignitability standard for hazardous waste #D001 if uncontaminated.**

---

## SECTION IX/ TRANSPORTATION

---

**DOT SHIPPING INFORMATION:** **Flammable liquids n.o.s**  
**(petroleum distillates)**

**HAZARD CLASS:** **3**

**IDENTIFICATION NUMBER:** **UN1268**

**PACKING GROUP:** **III**

**HAZARDOUS MATERIAL:** **Flammable Liquids**

N/A= NOT APPLICABLE

N/D=NOT DETECTED

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. THERE ARE NO GAURANTEES TO ITS ACCURACY OR SUITABILITY TO SPECIFIC APPLICATIONS. ACTUAL CONDITIONS OF USE, HANDLING, AND END PRODUCT PERFORMANCE ARE THE SOLE RESPONSIBILITY OF THE USER. THE USER ASSUMES ALL RISK AND LIABILITY FOR USE BEYOND THE STAMP STORE'S CONTROL, INCLUDING COMPLIANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

ISSURE DATE: 4/16/04