



CONCRETE TEXTURING TOOL & SUPPLY

45 UNDERWOOD ROAD
1-888-824-2383

THROOP, PA 18512
Fax 1-888-824-2353

www.concrete-texturing.com

KD-100

VOC Compliant Water-Based Cure & Seal

DESCRIPTION:

KD-100 is a water-based curing and sealing compound, as well as a dust-proofer for concrete. This product forms a water repellent and breathable film on freshly placed concrete.

USES:

Curing and sealing compound for commercial and industrial applications such as floors, parking decks, driveways and sidewalks. A good sealer for concrete slabs, aggregate, and dust proofing that dries to a low gloss, water repellent, mold, mildew and fungus resistant protective film.

APPLICATION:

Apply to a clean, dry, moisture-free substrate using a 3/8" or 1/2" nap roller or a pump sprayer.

Apply at a rate of 150-200 square feet per gallon depending on the surface porosity and texture.

Substrate temperature should be between 40 and 90 degrees. Avoid spraying in windy conditions as overspray may contaminate surrounding objects or landscape.

PRECAUTIONS:

KEEP FROM FREEZING. Keep out of reach of children. Wear protective clothing, gloves and safety glasses when applying. Avoid inhalation of vapors for prolonged periods of time.

Read MSDS for additional first aid information

PACKAGING:

KD-100 is available in 55- gallon drums and 5-gallon pails.

TECHNICAL DATA:

Solids..... % 15
Finish..... Low to Medium Gloss
Coverage..... 200-300 sq ft/Gallon
Drying Time (to touch)..... 1 - 2 hours
Drying Time (traffic)..... 12 - 15 hours
Application Temperature.. Above 40 Degrees F
Dried film is USDA approved
VOC Content..... < 250 grams/liter
Clean up with soap and warm water.

SPECIFICATIONS:

2500 LV meets or exceeds ASTM-C 309
Type 1, Class A, ASTM C 1315 Type 1,
Class A and AASHTO-M-148
Specifications for moisture retention

WWW.CONCRETE-TEXTURING.COM