



## IMPERIAL FINISHING PASTE

### TECHNICAL DATA & APPLICATION INSTRUCTION

#### PRODUCT DESCRIPTION

**Imperial Finishing Paste** is a trowel grade polymer modified cementitious topping for use as a void filler, and concrete smoothing compound. May also be used as micro topping for creating interesting decorative effects on concrete countertops & interior concrete floors. Imperial Finishing Paste may be integrally colored with liquid or granulated pigments. May also be stained with Acid Stain, scored, sanded, sand blasted, stenciled and sealed like plain concrete.

#### BENEFITS/FEATURES

- Non-flammable, non-combustible, non-corrosive.
- Economical, Easy clean-up.
- Minimal toxicity.
- Superior bonding ability.
- Available in white or gray.

#### RECOMMENDED APPLICATIONS

**Imperial Finishing Paste** is for filling pin-holes, micro-bubbles and small voids. It can also be used as a concrete-smoothing microtopping or to create decorative effects on a concrete surface. An aggregate additive is available for deeper voids filled for grouting or for filling voids created by the hand-pressed method.

#### TECHNICAL INFORMATION

Drying Time.....Overnight	Wet Appearance.....White or Gray
Re-Coat Time.....4 hours	Dry Appearance..... White or Gray
Application Temp.....50°F - 85°F	VOC Content.....N/A
	Concrete Adhesion.....Superior

**\*\*NOTE:** low air temperature, concrete temperature, relative humidity & water usage may all effect/extend drying times.

#### SPECIFICATIONS/COMPLIANCES

Imperial Finishing Paste is VOC and OTC compliant in all areas of the United States and many foreign countries.

#### APPROXIMATE COVERAGE RATES

Coverage Rates depend on water usage.

#### SHELF LIFE & PACKAGING

Imperial Finishing Paste has a 2 year shelf life in it's original, sealed unopened container. Once opened protect from moisture intrusion. Imperial Finishing Paste comes in Gray or White and is packaged in a 1 gallon pail (wt. 8 lbs).

#### INSTRUCTIONS FOR USE

**Preparation:** Substrate must be structurally sound, clean and dry. All flaking, scaling, dusting and any loose material must be removed by mechanical means or acid etching to produce a contaminant free surface. Acid etching requires a neutralization of the surface to restore a 7 PH balance.

1. Add clean potable water to achieve a paste or putty-like consistency. Be careful not to over water Imperial Finishing Paste.
2. Apply Imperial Finishing Paste into voids with consistent pressure on putty knife or trowel, completely filling the voids.
3. Allow Imperial Finishing Paste to dry overnight. Sand and clean off any dust from the sanding. Check the voids for proper fill. Steps **one** through **three** may need to be repeated to achieve complete fill of all voids.
4. Decorative Effects: Trowel finishing Paste onto countertop or concrete surface to achieve the desired decorative effect. Sand to a smooth surface colorize as desired, and seal.

#### SPECIAL NOTES

Please consult Material Safety Data Sheet (MSDS) and read warranty information prior to use.

DISTRIBUTED BY:

