



“NATURAL LOOK” PENETRATING SEALER

AN INVISIBLE WATERBASE SEALER FORMULATED TO IMPART WATER REPELLENCE AND DIRT REDUCTION TO CONCRETE, TILE & MASONRY SURFACES WITH NO CHANGE IN SURFACE APPEARANCE.

MAY BE USED AS A PRESEALER OR GROUT RELEASE ON TILE AND MASONRY SURFACES.

PRODUCT DESCRIPTION

This sealer reacts with carbon dioxide and atmospheric moisture to form a penetrating water repellent barrier within 24 hours. The extreme low moisture absorption provided by this sealer shows little change for up to ten years.

USES

- Mexican Tile • Brick • Flagstone
- Concrete • Artificial Stone
- Slate • Stucco • Quarry Tile • Clay Tile

FEATURES

- Use Indoors or Outdoors
- Non-Flammable
- Invisible Protection
- Water Repellent
- Long Lasting
- Water Clean Up
- Repels Dirt and Waterborne Stains

SPECIAL FEATURES

- Reduces Efflorescence Problems.
- Environmentally Safe.
- Mildew Resistant.
- Resists Freeze/Thaw Effects.
- Waterproofs Shower Grout and Glass Block Grout.

100 to 700 square feet per gallon depending on the porosity of the surface.

SPECIFICATIONS

FILM BREATHABLE	+50
COLOR (Invisible When Dry)	Light Straw
BASE	Sodium Methyl Siliconate
FLASH POINT	(Open Cup) None
PH:	Less Than 12
SOLVENT: (Thinner)	Water

PACKAGING

Glaze 'N Seal “Natural Look” Penetrating Sealer is packaged in Quarts, Gallons, 5 Gallon Pails and 55 Gallon Drums.

5 YEAR WARRANTY

Glaze 'N Seal warrants that their penetrating sealer, when used with compatible substrates, and according to stated application methods, will retain its water repellency for a period of 5 years from the date of application. In the event of a claim under this warranty, **Glaze 'N Seal** will furnish sufficient sealer to restore repellency. **Glaze 'N Seal** will not be liable for damage to the contents of the structure or for consequential incidental damages.

DO NOT allow excess sealer to dry on surface or a white residue may occur. (Read note on back before using the product.)



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA

FS 14-09/03



“NATURAL LOOK” PENETRATING SEALER PREPARATION & APPLICATION INSTRUCTIONS

PREPARATION

All surfaces must be clean, free of dirt, grease, wax, detergents and efflorescence. Do not allow any cleaning residue to remain. Surfaces cleaned with muriatic acid must be neutralized prior to sealer application. **Glaze 'N Seal Neutralizing Rinse** or similar product is recommended. Where suitable, high pressure water is an effective cleaning method. Gloves and goggles should be worn during application of sealer.

APPLICATION

Prior to applying sealer always test a small area to verify penetration and satisfaction of appearance. Allow 24 hours to dry and cure.

POROUS SURFACES

Apply to saturation with brush, roller or spray device, one liberal coat. However, DO NOT allow any excess sealer to remain on the surface.

IMPORTANT NOTE

Any Sealer not absorbed in 1 to 2 minutes must be immediately removed by wiping and polishing with dry absorbent rags to avoid a white residue on the surface. On vertical surfaces start at the top and work down keeping a “wet edge” at all times. Avoid run-down and overlapping. In 4 hours, substrate can be tested for water repellency by sprinkling water drops on surface. If water beads and does not penetrate, repellency is satisfactory. On exceptionally porous surfaces, a second coat may be necessary. If applying a second coat, it is critical not to allow ANY sealer to dry on the surface.

DENSE SURFACES

Apply one light coat with a sponge, sponge mop or clean rag. Be extremely careful to remove any excess sealer from surface before it dries. Always test for suitability prior to total application. If test shows any sign of white precipitate it may be necessary to thin sealer (3 parts sealer to 1 part water) and retest. If visible precipitate continues, contact your supplier. Allow sealer to dry at least 24 hours to develop maximum water repellency.

CAUTIONS

Glass, aluminum, glazed tile and other surfaces should be protected from sealer contact. The alkalinity of this sealer will damage lawns and shrubs; protect with a drop cloth.

COVERAGE

100 to 700 square feet per gallon dependent on porosity of the surface and method of application. Apply sealer between 50° and 80°F. On warm days porous and semi-porous surfaces may be lightly dampened with water prior to sealer application. Do not apply sealer during rainy conditions or if rain is anticipated within two hours of application.

STORAGE

Do not allow to freeze.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA