



FAST DRYING MEDIUM SHEEN SLATE SEALER

FORMULATED SPECIFICALLY FOR SLATE, FLAGSTONE AND QUARRY TILE

PRODUCT DESCRIPTION

A clear acrylic waterbase finish designed to protect and beautify slate, flagstone and quarry tile. **Glaze 'N Seal Slate Sealer** protects against all organic stains including cooking oil, grease and beverages. It may be used indoors or outdoors and is extremely easy to apply and maintain.

USES

- **Waterseals, protects and improves appearance of all slate, flagstone and quarry tile.**
- **Use indoors and outdoors.**
- **Low sheen appearance eases clean up.**
- **May be used as grout release.**

FEATURES

- Repels oil and grease stains
- Nonflammable
- No harmful vapors
- Cleans up with water
- Easy to apply
- Water repellent
- Reduce efflorescence
- Recoatable
- Non-yellowing

PREPARATION

All surfaces must be free of efflorescence, dirt, oil, wax, grease and defective paints or sealers. If muriatic acid is used, all acid residue must be removed prior to application of sealer. Do not allow acid to dry. Use **Glaze 'N Seal Neutralizing Rinse** to neutralize surface before sealing.

STORAGE: Do not allow to freeze.

APPLICATION

Apply two or more coats of sealer (do not allow it to puddle). Make sure each coat is dry to the touch before applying second coat; usually one to two hours.

Allow additional drying time in moist, cool climates. It can be applied with a sponge mop, lambs wool applicator or

spray-equipment dependent on porosity and roughness of surface. Clean tools with water before sealer dries. Apply between 55°F and 80°F. If it is necessary to apply sealer on a warm day in direct sunlight, slightly dampen the surface to be sealed with a fine spray of water prior to application of the sealer. Allow 72 hours curing time against heavy moisture and bulk water. Sealer will continue to gain strength for up to one week.

Note: Always test a small area of surface to be sealed to verify penetration and satisfaction of sealed appearance.

SPECIFICATIONS

BASE	Aqueous Acrylic Co-Polymer
TUKON HARDNESS	+6.0
FRICITION LEVEL	Excess 6.3
GLASS TRANSITION POINT	34C
DENSITY	8.58 pounds per gallon
REFRACTIVE INDEX	Approx. 1.4077
APPEARANCE	Milky White – Dries Clear

COVERAGE

100 to 600 square feet per gallon depending on the porosity of the surface.

MAINTENANCE

Glaze 'N Seal Floor Polish is recommended as a protective finish over the sealer (indoors only). This will protect the sealer and extend sealer life significantly. Sweep and damp mop floor frequently. Use **Glaze 'N Seal Neutral Cleaner** to clean floor as necessary.

PACKAGING

Concrete, Tile and Masonry Sealer is packaged in quarts, gallons, 5 gallons and 55 gallon drums.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA

FS 39-3/03